



6.0/6.5
6.0/6.5
6.0/6.5

17.0
17.0
16.5

TOT 62.5/63.0 HML L2 TIER 1
CAP 61.0/61.5 CML L2 TIER 1
TOT 59.0/59.5 GML L2 TIER 1

17.0
17.0
16.5

22.5
21.0
20.0

DRAFT

	MINIMUM LOAD RATING	SMALLEST TYRE SIZE
STEER	144	11R22.5
DRIVE	140	275/70R22.5
TRAILER/DOLLY	140	255/70R22.5

TRUCK	9.0
TRAILER	8.0

NOTES:

- PAYLOAD HEIGHT MAY BE RESTRICTED INDIRECTLY BY MAXIMUM BIN HEIGHT.
- TRUCK REAR OVERHANG CANNOT EXCEED 60% OF TRUCK WHEELBASE.
- TRAILER REAR OVERHANG CANNOT EXCEED 60% OF DIMENSION C.
- ELIGIBLE VEHICLES MUST COMPLY WITH TIER 1 MASS LIMITS.

REV.	DESCRIPTION	SLW DRN.	SDT APPR.	DATE
A	DRAFT RELEASE			23 FEB 2024

ADVANTIA
TRANSPORT CONSULTING

T: (03) 9438 6790
E: contact@advantia.com.au
W: www.advantia.com.au

TITLE
22M 6X4 TRUCK & 5-AXLE DOG TRAILER – VEHICLE SPECIFICATION ENVELOPE

ALL DIMENSIONS IN MM. TOLERANCES: THE LESSER OF ±20 OR ±1% UNLESS OTHERWISE SPECIFIED. VERTICAL DIMENSIONS ARE MEASURED IN LADEN CONDITION. CERTIFIERS MAY ADD 20MM FOR UNLADEN CONDITION.	SHEET 1 of 1 SCALE NTS SIZE A3	CLIENT ADVANTIA TRANSPORT CONSULTING DWG NO. ATC3214-L-02	REV. A
--	---	--	-----------