



6.0/6.5	17.0	TOT 68.0/68.5 HML L2 TIER 1	22.5	22.5
6.0/6.5	17.0	CAP 64.5/65.0 CML L2 TIER 1	21.0	21.0
6.0/6.5	16.5	TOT 62.5/63.0 GML L2 TIER 1	20.0	20.0

DRAFT

	MINIMUM LOAD RATING	SMALLEST TYRE SIZE
STEER	144	11R22.5
DRIVE	140	275/70R22.5
TRAILER	140	255/70R22.5

TRUCK	9.0
TRAILER	8.0

- NOTES:
- PAYLOAD HEIGHT MAY BE RESTRICTED INDIRECTLY BY MAXIMUM BIN HEIGHT.
  - TRUCK REAR OVERHANG CANNOT EXCEED 60% OF TRUCK WHEELBASE.
  - TRAILER REAR OVERHANG CANNOT EXCEED 60% OF DIMENSION C.
  - ELIGIBLE VEHICLES MUST COMPLY WITH TIER 1 MASS LIMITS.

<p><b>ADVANTIA</b> TRANSPORT CONSULTING</p> <p>T: (03) 9438 6790 E: contact@advantia.com.au W: www.advantia.com.au</p>		<p>TITLE 27M 6X4 TRUCK &amp; 6-AXLE DOG TRAILER – VEHICLE SPECIFICATION ENVELOPE</p>	
		<p>ALL DIMENSIONS IN MM. TOLERANCES: THE LESSER OF ±20 OR ±1% UNLESS OTHERWISE SPECIFIED. VERTICAL DIMENSIONS ARE MEASURED IN LADEN CONDITION. CERTIFIERS MAY ADD 20MM FOR UNLADEN CONDITION.</p>	<p>SHEET 1 of 1 SCALE NTS SIZE A3</p>
<p>REV. A</p>	<p>DESCRIPTION DRAFT RELEASE</p>	<p>SLW SDT DRN. APPR.</p>	<p>23 FEB 2024 DATE</p>